

K80YN-W-W



4" new construction LED downlight

Weight: 5.32 lbs lbs

Project:

Type:

Prepared By:

Date:

Driver Info

Type	LED
120V	0.17A
208V	0.11A
240V	0.10A
277V	0.09A
Input Watts	20.3W
Efficiency	99%

LED Info

Watts	20W
Color Temp	3500K
Color Accuracy	82 CRI
L70 Lifespan	50,000
Lumens	1626
Efficacy	80.2 LPW

Technical Specifications

Listings

UL Listed:

Suitable for wet locations covered ceiling

ENERGY STAR V2.0:

This product is ENERGY STAR® Version 2.0 Certified.

Construction

Housing:

Professional-grade, die-cast aluminum construction

Trim Ring:

White powder coated die cast trim ring

Trim Cone:

White square trim cone

Drop Ceiling Installation:

NDLED can be installed in drop ceiling tiles when using optional c-channel bars and following local construction codes

Aperture Size:

4" Trim Module

Junction Box:

Integral junction box with wiring capacity for
Min 90°C supply conductors
4 in 4 out

Easy Installation:

The EZ-Connector makes installation easy

Ambient Temperature:

Suitable For use in 40°C (104°F)

Cold Weather Starting:

Minimum starting temperature is -40°C (-40°F)

Aperture Size:

4" Rough-In

Air Tight:

Housing certified Air Tight as per ASTM E283

Mounting:

Housing includes nailer bars and butterfly brackets. Brackets also accommodate mounting with 1/4" to 1/2" bar stock, C channel or 1/2" conduit.

Easy Installation:

The EZConnector makes installation easy

Thermal Protector:

Thermal protector included. Disables power if temperature exceeds safe operation levels.

Electrical

Dimming:

Dimmable. Requires rough-in with dimming driver.

Dimming Driver:

0 - 10V (at 120-277V), TRIAC and ELV (at 120V only).
www.rablighting.com/images/downlights_dimmer.png

Driver:

ELV, 0-10V and TRIAC Dimming, Constant Current, Class 2, 120V-277V, 50/60Hz, Power Factor 98%, THD ≤ 20%

Optical

Optics:

Wall wash optics engineered for wide lateral distribution and smooth soft light from ceiling to floor

LED Characteristics

Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

K80YN-W-W

Dimensions: ND4S20D

